



“Bioelectricity Production from River Waste Water”

Seema D. Sherkar^{1*}, Pratik D. Kamthe², Ujwala V. Khisti³, Neha N. Patil⁴

1 Department of Microbiology, PDEA's Annasaheb Magar Mahavidyalaya, Hadapsar, Pune-411028, Maharashtra, India

*Corresponding author: Seema D. Sherkar*sherkars1988@gmail.com*

ABSTRACT:

*Bioelectricity is one of the major non conventional forms of the energy. The aim of this systematic study was to update the current state of research and to evaluate biological effects of static electric field. Developmental bioelectricity refers to the regulation of cell, tissue, and organ-level patterning and behaviour as the result of endogenous electrically mediated signaling. Cells and tissues of all types use ion fluxes to communicate electrically. The charge carrier in bioelectricity is the ion (charged atom), and an electric current and field is generated whenever a net ion flux occurs. Endogenous electric currents and fields, ion fluxes, and differences in resting potential across tissues comprise an ancient and highly conserved communicating and signaling system. In this current study MFC (Microbial Fuel Cell) from river waste water was prepared. These MFC contain copper wire (2.0 mm) as anode and aluminum plates as the cathode. When consistently water quality indices were checked, we found 10 % reduction in the values of BOD and COD. In this study we can see the continuous production of potential difference of 2 volts. It was also observed that Potential difference was increased after addition of 5% Methyl Orange within the river waste water. The 5 days of Incubation period, increase in the potential difference was observed. Current study of the isolates confirmed that they have ability to convert organic matter of river waste water to nitrate and nitrite by nitrification process. In further study, the fish toxicity assay was performed using the selected *Cyprinus carpio* (Common carp) and *Poecilia reticulata* (Gappi) and found to have zero mortality rates after treatment.*

Keywords: Bioelectricity, Nitrification process, Fish toxicity, Water quality indices.

Received 28.04.2023

Revised 20.05.2023

Accepted 11.06. 2023

INTRODUCTION:

Our regular life is totally dependent on electricity. Be it Lights, Fans, escalators, vehicles on the road, water supply to home; almost everything requires energy-“The electrical energy”. Now a days electricity has reached to remote areas. Thus resultant requirement of electricity is very high. Alongwith conventional production, bioproduction of electricity is very essential [12]. A way has been studied towards Green Energy. Bioelectricity is produced by the different phenomenon like electron transport chain reaction and glycolysis. Microorganisms also show potential to produce bioelectricity. Bacterial cultures also have ability to produce potential difference. For this Purpose we need to accessorize the bacteria with MFC (Microbial Fuel Cell).MFC is nothing but the apparatus which required to collect the electrons. The study of MFC was first used by [1][2] to generate electricity the *E. coli*. and electrodes. Biochemical fuel system generate electric current by diverting electrons produced in redox reaction. In MFC the anodes perform as electron donor and oxidizes compound and the cathodes perform as oxidizing agent or electron acceptor. MFCs can be grouped into two general categories: Mediated and Unmediated. In early 20 th century, Mediated MFCs were common.

The mediator used for this was chemicals. Unmediated MFCs emerged in the 1970 in this type of MFCs bacteria are mediators and typically have electrochemical activity due to redox proteins such as Cytochrome on their outer membrane. In the 21st century MFC have started to find commercial use in waste water treatment. For the preparation of MFC reuse able plastic containers were used. Then these containers are attached with cathode (aluminum sheet) and anode (copper wire 2.0 mm). Then MFCs are connected in series to complete the circuit along with multimeter. The first reading of the sample was noted as ± 1.019 m volt. Microbial fuel cells (MFC) are having operational or functional advantages over the technologies currently used for generating energy from waste water. This study showed that production of large amount of electricity can be produce which can be used for household or small scale use. The bioelectricity production can be future project to be a good solution over a big problem of shortage of electricity and waste water management [5].

MATERIAL AND METHODS:

Collection of sample: Sample of River waste water was collected in month of March, 2022 from local area of MulaMutha river, Manjari (Pune, Maharashtra)[6][7].

Preparation of MFC:

Microbial fuel cell (MFC) set up was prepared by using reusable plastic bottles. These bottles were attached with cathode (Aluminum Sheet) and anode(Copper wire 2.0 mm).

Checking of water Quality indices:

The Physico-chemical parameters such as Biological Oxygen Demand (BOD) and Chemical Oxygen Demand (COD))were analyzed at first day and five days using standard manual protocol.

The voltmeter is connected in a circuit in parallel to measure the voltage in the circuit[8][9].

In this study we have checked different water quality indices as Biochemical Oxygen Demand (BOD), Chemical Oxygen Demand (COD), total suspended solids (TSS),Temperature and pH. In first observations COD values of the river waste water were high. COD of sample was in a range 600 to 900 mg/l. After treatment it showed 10 % reduction in COD values [3][4].

Determination of fish toxicity assay:

Aquatic Toxicity of river waste water was measured by fish bioassay. A river waste water can be tested for this criterion by placing some waste in a test water tank and introducing .The fish toxicity assay (RAR) was conducted with the selected *Cyprinus carpio* (Common carp) and *Poecilia reticulata* (Gappi) fishes. *Mtsya beej kendra* (Hadapsar) showed zero mortality rate at different concentration. At room temperature for 96 hours of incubation.[10] (Table 5)Waste is hazardous by aquatic toxicity1 if a 96-hour LC50 is less than 500 mg/liter.96-hourLC50 < 500 mg/l = acute aquatic toxicity For more information, here is the procedure for the acute aquatic toxicity bioassay per [11].

Bioelectricity generation from algal biomass using microbial fuel cells(MFCs)

A six chambered MFC was constructed. Two holes of diameter 5 mm were made on each bottle lids for the insertion of the salt bridge and electrodes. Take a 700 ml river waste water sample in each microbial fuel cell. Then the circuit was completed by using electrical wire 0.5 mm . And LED bulb connected to anode and cathode, and then observe for electricity generation; By checking if the bulb glows or not[1][2][3].

RESULTS AND DISCUSSION:

The experiment of bioelectricity was carried out for 120 hours i.e. 5 days in aerobic and anarobic conditions.Outcome of these experiments showed bioelectricity production from Riverwater sample.

Different water quality indices such as Tempreture, pH , BOD,COD were checked.During the treatment there were no fluctuations in temperature.(Table 3.1)

[H+] ion potential plays very important role in Microbial Life cycle. During this whole process of bioelectricity production. Ther were no fluctuations in pH values.(Table 3.2)

pH values of river waste water was continuously checked by using pH meter and pH indicator strip

This is composed of naturally occurring microorganisms and organic load from commercial as well as Nitrifying biomass material. The potential difference is directly proportional to the number of microbial fuel cells (MFCs) and its seasonal condition whereas it is also dependent upon organic material present in it.

Table No3.1: Temperature of Five days







Temperature	Day1	Day2	Day3	Day4	Day5
Blank	31 ⁰ C	31 ⁰ C	31 ⁰ C	31 ⁰ C	31 ⁰ C
Sample	31 ⁰ C	32 ⁰ C	32 ⁰ C	34 ⁰ C	34 ⁰ C

Table2.3.2: pH of Five days:

pH	Day1	Day2	Day3	Day4	Day5
Blank	7	7	7	7	7
Sample	6	6	7	7	7

Table5: Determination of fish toxicity assay of Aqua RAR formulation

Recommended Family	Recommended Fishes	After treatment mortality rate is because no any death of fishes occur in water sample after treatment of MFC				
		DAY1	DAY2	DAY3	DAY4	DAY5
Cyprinidae	<i>Cyprinus carpio</i>	10	10	10	10	10
Poeciliidae	<i>Poecilia reticulata</i>	10	10	10	10	10

 <p>Fig No 1: Collection of sample from Mula Mutha river</p>	 <p>Microbial Fuel Cells with electricity generated</p>	 <p>Fig. No.1. Microbial Fuel Cells Bottle</p>
 <p>Fig. No.2. Microbial Fuel Cells Material</p>	 <p>Fig. No.3. Microbial Fuel Cells with electricity generated</p>	 <p>Fig. No.3. Microbial Fuel Cells with electricity generated</p>

CONCLUSION:

Bioelectricity production was carried out by microbial fuel cells [MFC] by using river waste water sample. This waste water sample was checked for its potential to generate bioelectricity under aerobic and anaerobic conditions. The experimental data showed the electricity generation by gradual increase from Day 1 to Day 15. Fish toxicity assay revealed that treated water is safe to release in normal water bodies. The BOD and COD values and bioelectricity production of waste water sample was declined at the end of experiment.

REFERENCES:

1. Logan, Bruce E.; Hamelers, Bert; Rozendal, René; Schröder, Uwe; Keller, Jürg; Freguia, Stefano; Aelterman, Peter; Verstraete, Willy; Rabaey, Korneel (2006). "Microbial Fuel Cells: Methodology and Technology". *Environmental Science & Technology*. **40** (17): 5181–5192. doi:10.1021/es0605016. PMID 16999087.
2. Potter, M. C. (1911). "Electrical Effects Accompanying the Decomposition of Organic Compounds". *Proceedings of the Royal Society B: Biological Sciences*. **84** (571): 260– 76. Bibcode:1911RSPSB..84..260P. doi:10.1098/rspb.1911.0073. JSTOR 80609.
3. Kim, BH.; Chang, IS.; Gil, GC.; Park, HS.; Kim, HJ. (April 2003). "Novel BOD (biological oxygen demand) sensor using mediator-less microbial fuel cell". *Biotechnology Letters*. **25** (7): 541– 545. doi:10.1023/A:1022891231369. PMID 12882142. S2CID 5980362.
4. Chang, In Seop; Moon, Hyunsoo; Jang, Jae Kyung; Kim, Byung Hong (2005). "Improvement of a microbial fuel cell performance as a BOD sensor using respiratory inhibitors". *Biosensors and*

- Bioelectronics*. **20** (9): 1856–9. doi:10.1016/j.bios.2004.06.003. PMID 15681205.
5. Heidrich, E. S; Dolfing, J; Scott, K; Edwards, S. R; Jones, C; Curtis, T. P (2012). "Production of hydrogen from domestic wastewater in a pilot-scale microbial electrolysis cell". *Applied Microbiology and Biotechnology*. **97** (15): 6979–89. doi:10.1007/s00253-012-4456-7. PMID 23053105. S2CID 15306503.
 6. Bogdanov, Dmitrii; Farfan, Javier; Sadvoskaia, Kristina; Aghahosseini, Arman; et al. (2019). "Radical transformation pathway towards sustainable electricity via evolutionary steps". *Nature Communications*. **10** (1): 1077. Bibcode:2019NatCo..10.1077B. doi:10.1038/s41467-019-08855-1. PMC 6403340. PMID 30842423.
 7. Miller, Joe (9 September 2020). "Hydrogen takes a back seat to electric for passenger vehicles". *FinancialTimes*. Archived from the original on 20 September 2020. Retrieved 20 September 2020.
 8. Ganjar Samudro, Sarwoko Mangkoedihardjo Review on BOD, COD and BOD/COD ratio: A triangle zone for toxic, Biodegradable and stable levels. *International journal of academic research* vol.2. No.4 July 2010.
 9. 19th edition of standard methods for the examination of water and wastewater, at APHA's manual.
 10. Alabaster, J.S., Abram, F.S.H., 1964. Development and use of a direct method for evaluating toxicity in fish. In: *Advances in Water Pollution Research*. Pergamon Press, Oxford, pp. 41–54. DOI: 10.1016/B978-0-08-011438-5.50011-8 Corpus ID: 132308677; 11)22 CCR Section 66261.24(a)(6)
 11. Nations Climate Change Conference 2022 COP27, Egypt, November 2022.

CITATION OF THIS ARTICLE

Seema D. Sherkar, Pratik D. Kamthe, Ujwala V. Khisti, Neha N. Patil: Bioelectricity Production from River Waste Water. *Bull. Env. Pharmacol. Life Sci., Spl Issue [2]: 2023: 154-157.*